

Tora

SRX 5800/6800

SN 6800 V



NEW TORA SERIES

The **TORA** series was conceived as a range of medium-power tractors for professionals characterized by upgraded hydraulics, mechanical equipment and operator comfort. The underlying principle is that fuel consumption and running costs must be taken into account in all agricultural applications, and that the power delivered by the tractor should always be commensurate with the task to be performed, thereby ensuring maximum efficiency with minimum wastage of time and effort.

ANTONIOCARRARO.COM



N°1 SPECIAL TRACTORS

TECHNICAL DATA:

SRX 5800/6800 - SN 6800 V

| | | |
|-------------------------|---|---|
| Frame | ACTIO™ integral oscillating frame • RGS™ reversible drive system (SRX) • Unidirectional (SN) • Articulated frame • Four equal-size wheels • Rear final drives | |
| Engine type | Diesel with common rail direct injection, with turbo and intercooler on the 6800 Emissions Standard: Stage 5 No. of cylinders: 4 - 8 Valves Rated rpm: 2600 Tank capacity (litres): 40 | Power kW/CV (97/68/CE): 37.9/ 52 (5800) 48.5/ 66 (6800) Max torque (Nm@rpm): 170 Nm/1690 (5800) 210 Nm/1690 (6800) |
| Transmission | S90: 32 speed synchronised gearbox: 16 FWD + 16 REV with synchronised shuttle. Electrohydraulic control of rear differential lock; mechanical control of front differential lock. Permanent all-wheel drive | |
| Power take-off | Rear, independent 540/540E rpm with progressive electro-hydraulic engagement; synchronised groundspeed | |
| Shaft | 6 spline 1 3/8" shaft with easy coupling | |
| Hydraulic system | Load sensing hydraulic system. Rear auxiliary hydraulic system with 1 double-acting remote valve with float and 1 oil return (3 rear hydraulic couplers). Pump capacity 37 l/min | |
| Rear power lift | Hydraulic lift with 3-point linkage Lifting capacity at the hitch balls (kg): 2190 Oscillating lift arms and lateral stabilizer bars, Cat. 1-2; Category "C" height-adjustable rear tow hook | |
| Steering | Hydraulic 2 piston | |
| Brakes | Rear service brakes: oil-immersed dual discs with hydraulic control; Combination parking brake: band brake on transmission and integrated mechanical Superbrake system acting on blocks. | |
| Platform | Suspended on Silent Blocks | |
| Weight | SRX roll-bar 1775÷1965 kg SN roll-bar 1175÷1965 kg | SRX cab. 1925÷2115 kg SN cab. 1925÷2115 kg |

